

Mechanical temperature switches

Type T1X - T2X

with capillary for hazardous areas

Features

- Single switch T1X and dual switch T2X with remote sensor
- Explosion proof housing
- Terminal clip integrated, set point adjustment in C and °F under tamper protected cover
- Protection class: IP65, NEMA 4 / 7 / 9
- Optional:
 - for T1X: adjustable hysteresis (switch-back difference), S-micro switch
 - Special version for trace heating systems with ratings up to 32 A / 220 V (22/32A / 380 V AC) on request
 - Approvals: Ex d, Ex ia, UL, CSA

Adjustment ranges

-45 °C...+66 °C to +160 °C...+316 °C

Applications

Temperature monitoring and control
in chemical industry and oil industry, offshore



Technical Data

Housing material:	Die-cast aluminium, painted
Temperature sensor material:	304 stainless steel (1.4301)
Temperature sensor type:	Capillary, 1.8 m long (6 foot) (optional 3.6 m and 7.5 m) (12 and 25 foot), armoured If not equipped with thermowell the sensor may only be used up to 21 bar max.
Electrical values:	All models are equipped with SPDT contacts.
Micro switch type:	H, M, GH, GM, S
Electrical connection:	From the terminal block through a 1/2" NPT conduit connection (T1X) resp. a 3/4" NPT conduit connection (T2X) outside.

Protection class:	IP65, NEMA 4 / 7 / 9
Set point adjustment:	Turn adjustment knob clockwise to increase the actuation point
Standards:	The equipment is in conformity with the following harmonised European standards: EN 60014 1977 + A1 to A4 and EN 500120 1977 + A1
Intrinsic safety:	The switches are also suitable for inherent safety applications. Add "Exi" in case of ordering. The following max. values are valid when using these switches: Umax = 28 V I _{max} = 50 mA
Approvals:	Ex d, Ex ia, UL, CSA
Weight:	T1X: approx. 2.1 kg; T2X: approx. 2.9 kg

Adjustment ranges

Code adjustment range	Sensor temperature limits (°C)	Adjustment range (°C)	Hysteresis (°C)* for micro switch		
			H, GH	M, GM	S
154	-73 ... +93	-45... +66	0.5... 1.1	1.1... 2.2	2.2... 8.3
251	-73 ... +149	+10... +121	0.5... 1.1	1.1... 2.2	2.2... 8.3
351	-73 ... +205	+66... +177	0.5... 1.1	1.1... 2.2	2.2... 8.3
601	-18 ... +343	+149... +227	1.1... 2.2	2.2... 3.3	1.6... 2.7
603	-18 ... +343	+160... +316	1.1... 2.2	2.2... 3.3	1.6... 2.7

* dependent on medium

Techniquip Ltd
The Old Brewery
Norton Fitzwarren
Taunton
TA2 6RN
Tel 01823-351255



Type T1X - T2X

Barksdale